

# PREHEATER



The PreHeater is ideal for rendering and fishmeal processing, with inputs of varying quality and composition, requiring minimal pre-cooking preparation. Customers can freely choose the type of equipment from a production range of 2–50 t/h, and the steam supply regulator can easily handle even small volumes of steam when required.



## HEADQUARTER

PT ARSI INDO GRAHA  
INDONESIA

+6281270762750  
info@arsiindograha.com  
www.arsiindograha.com

## GLOBAL OFFICE

RC INDO GROUP LIMITED  
RWANDA

+250793885693  
info@rcrwanda.com  
www.rcrwanda.com

ARSYI GLOBAL L.L.C-FZ  
DUBAI

+971507169760  
info@arsyi.com  
www.arsyi.com

# PREHEATER

| Type   | Capacity(t/h) | Length | Height | Width | Weight (metric ton) |
|--------|---------------|--------|--------|-------|---------------------|
| FC0605 | 2.6-3.5       | 3350   | 1050   | 1200  | 4                   |
| FC0806 | 6.4-8.0       | 8250   | 1850   | 1850  | 12                  |
| FC0808 | 8.8-11.0      | 10200  | 1850   | 1850  | 14                  |
| FC1108 | 12.8-16.0     | 10900  | 2350   | 2200  | 20                  |
| FC1110 | 16.0-20.0     | 12800  | 2350   | 2200  | 23                  |
| FC1112 | 20.0-25.0     | 14850  | 2350   | 2200  | 27                  |
| FC1310 | 20.0-25.0     | 13050  | 2450   | 2200  | 32                  |
| FC1312 | 24.0-30.0     | 15050  | 2450   | 2200  | 36                  |
| FC1314 | 28.0-35.0     | 17050  | 2450   | 2200  | 40                  |
| FC1612 | 30.4-38.0     | 15150  | 3450   | 2400  | 40                  |
| FC1614 | 35.2-44.0     | 17150  | 3450   | 2400  | 47                  |
| FC1616 | 40.0-50.0     | 19150  | 3450   | 2400  | 55                  |



## HEADQUARTER

PT ARSI INDO GRAHA  
INDONESIA

+6281270762750  
info@arsiindograha.com  
www.arsiindograha.com

## GLOBAL OFFICE

RC INDO GROUP LIMITED  
RWANDA

+250793885693  
info@rcrwanda.com  
www.rcrwanda.com

ARSYI GLOBAL L.L.C-FZ  
DUBAI

+971507169760  
info@arsyi.com  
www.arsyi.com