

Double-Layer Belt-Type Fish Processing Line RCF-828



Primarily used for cleaning, de-scaling, and washing products. Raw material and wastewater are separated. Hygienic and easy to clean. Mainly used in fish fillet processing enterprises.

Equipment Configuration:

The main frame of the equipment is welded using 50*50*2.0mm stainless steel square tubes. Moving parts are made of 6-8mm stainless steel. The front and rear main rollers are 10mm thick stainless steel. The rear of the conveyor belt can be lifted for easy cleaning of the bottom of the belt. Imported mildew-proof sanitary belts are used. The thickness of the worktables on both sides is 2.0mm, and wastewater is collected uniformly. The upper and lower belt motors are Mitsubishi frequency conversion speed regulation, suitable for 10-12 people to operate simultaneously, suitable for open-back fish processing and fish fillet processing. Length can be customized.

Model	RC-828 Double-Layer Belt Fish Processing Line
Length	Customizable
Power	Customizable
Classification	Conveyor line series



JARVIS®

HEADQUARTER

PT ARSI INDO GRAHA
INDONESIA

☎ +6281270762750

✉ info@arsiindograha.com

🌐 www.arsiindograha.com

GLOBAL OFFICE

RC INDO GROUP LIMITED
RWANDA

☎ +250794034060

✉ info@rcrwanda.com

🌐 www.rcrwanda.com

ARSYI GLOBAL L.L.C-FZ
DUBAI

☎ +971507169760

✉ info@arsyi.com

🌐 www.arsyi.com