

Twin-screw Press



The twin-screw presses are often used to extract liquid from cooked fish or meat as part of low-temperature wet rendering processes. They can also be used in high-capacity feather plants.

BENEFITS :

- Higher solids content in press cake than with decanter centrifuges
- efficient continuous fat extraction
- Easy to operate and monitor using advanced control system
- Easy to connect to odor control system, to minimize impacts
- Exceptional service life
- Easy to refurbish when they finally wear out

Type	Capacity(t/h)	Dimension(L)	Dimension(W)	Dimension(H)	Weight(mt)	Power(kW)
TP24	2.5	4400	1250	1030	3	7.5-11
TP35	5	5460	1800	1300	7	11-18.5
MS 41	13	4600	2000	1500	9.5	22-37
MS 49	18	5700	2400	1950	15.5	30-55
MS 56	25	6700	2500	1870	23	45-75
MS 64	40	7400	2800	2100	31	90-110
RS64	50	8350	2800	2100	34	110-132
XS88F	60	8400	2850	2165	46	95-132



JARVIS®

HEADQUARTER

PT ARSI INDO GRAHA
INDONESIA

☎ +6281270762750

✉ info@arsiindograha.com

🌐 www.arsiindograha.com

GLOBAL OFFICE

RC INDO GROUP LIMITED
RWANDA

☎ +250794034060

✉ info@rcrwanda.com

🌐 www.rcrwanda.com

ARSYI GLOBAL L.L.C-FZ
DUBAI

☎ +971507169760

✉ info@arsyi.com

🌐 www.arsyi.com